

PRODUCT SPECIFICATIONS:

TALLYKEY T8



Height:
145 cm.

Weight:
60-80 Kg.

Power outlets:
16A to 250A one or three-phase.

Terminal connection:
Up to 630A.

Water taps:
Option for ½", ¾" or 1" water taps.

Safety:
Every outlet is protected by a MCB and RCD or RCBO.

Lighting:
1 x 9.5 watts LED.

Temperature:
- 20 to + 60-degree Celsius.

Density:
IP44 (IPx6 as option).

Standard:
IEC 61439-1 and IEC 61439-3.

Mounting:
Flanges: Delivered with standard flange for fixed foundation (concrete).

Power connection:
Cable lugs up to 25 mm wide (630A).

Light connection:
CU, 1.5 to 8 mm².

Water connection:
Up to 32 mm PL-pipes.

MATERIALS:
Pedestal: Weather-resistant, anodised aluminium
Lamp cover: Impact resistant plastic.
Screws and bolts: Acid-proof steel.

Maintenance:
None.

Subject to change without notice.

Agent: **AlfaBryggan AB - "Modern-Marin-Miljö"**

VD: Christer Ulfvengren
Tel: 08-391672
E-post: christer@alfabryggan.se
Hemsida: www.alfabryggan.se

